

Datasheet Conveyor Belt



**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 R 22/215 CR
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	PVC	
Thickness:	2		1,5	mm (approx.)
Colour:	Green	Green	Green	
Hardness:	55 Shore A		80 Shore A	
Profile:	CR		-	

Total thickness:	6,9		mm (approx.)
Weight:	6,4		kg/m² (approx.)
Max. width:	2000		mm
Belt support:	Rollers, Flat		
Rating at 1% elongation:	10		N/mm
Advised pretension:	4 - 7		N/mm
Maximum allowable tension:	20		N/mm
Temperature range:	-10	to	+80 °C
Minimum pulley diameters:			
Flexing:	100		mm
Backflexing:	150		mm

Special approval: Not applicable

Applications: Agricultural and horticultural industry
Bean picking and other harvesting machines

Date of issue 20-03-2014-2

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com